FUJITSU

Data Sheet
Fujitsu Accessory Thunderbolt™ 4 Port Replicator
A fast, easy and reliable solution for your computer

First Thunderbolt™ Port Replicator on the market providing enhanced security and full support of Intel® AMT (vPro®).
The universal port can easily connect almost everything with a single cable and high speed-data transfer. This smart workspace solution keeps your desk clean and tidy.

Features
- Full support of Intel® AMT (vPro®)
- USB charging LED
- 2x USB Type-C with Thunderbolt™ 4, 2x USB Type-C and 3x USB Type-A interfaces
- On/off button working with dedicated FUJITSU clients
- DisplayPort and HDMI
- PXE boot
- MAPT (MAC address path through)
- WoL (Wake on LAN)
- Supporting from 10th generation dedicated FUJITSU devices
- Downwards compatible supporting dedicated FUJITSU devices with Thunderbolt™ 3 and Type-C

Usability
- Instant access to your input devices, high speed LAN via one USB plug, supporting Thunderbolt™ 4 for Windows devices
- Keep your peripherals plugged-in and charged
- Having a clean desk and save space with a single cable connected to your client

Security and Manageability
- Supporting Intel® AMT (vPro®)
- Kensington lock support

Thunderbolt™ 4 Port Replicator

Technical specifications

Color	Black

Interfaces

Power on switch	Power on and off for dedicated Fujitsu products (does not support LIFEBOOK A and CELSIUS H7 Mobile WS)
DC-in	1 (20V/170W required)
USB Type-C (to Devices)	2x Type-C - 5 V/ 1.5 A, 4.5 W charging port 1x Type-C - TBT4 up to 60 W (PD v2.0-1.1), 5-20 V/3.0 A upstream (PC) 1x Type-C - TBT4 up to 15 W (PD v2.0-1.1), 5 V/3.0 A downstream, power output to client
USB Type-A	1x Type-A - 5 V/ 2.4 A, 12 W 2x Type-A - 5 V/ 0.9 A, 4.5 W
USB Type-C cable	1 Thunderbolt™ 4 Length: 0.70 m
DisplayPort	2x V1.4++ resolution up to 7680 x 4320@30Hz / 5120 x 2880@60Hz / 4096 x 2160@60Hz / 3840 x 2160@60Hz depending on system for 1 external display up to 7680 x 4320@24Hz / 4096 x 2160@60Hz / 3840 x 2160@60Hz for 2 external displays (with up to 5120 x 2880@60 Hz / 4096 x 2160@60Hz / 3840 x 2160@60Hz connected to 2nd DisplayPort) up to 7680 x 4320@30 Hz / 4096 x 2160@60Hz / 3840 x 2160@60Hz for 2 external displays (with 4096 x 2160@60Hz / 3840 x 2160@60Hz connected to HDMI) up to 3840 x 2160@60Hz (DP1 & DP2) / 3840 x 2160@30Hz (HDMI) for 3 external displays connected to 2 x DP and HDMI in parallel - w/o internal display on up to 3840 x 2160@60Hz (DP1 & DP2) / 3840 x 2160@30Hz (HDMI) for 3 external displays connected to 2 x DP and HDMI in parallel - with additional internal display on (4 displays in total)
HDMI	1 V 2.0b resolution up to 4096 x 2160@60Hz / 3,840 x 2160@60Hz depending on system for 1 external display up to 4096 x 2160@60Hz / 3840 x 2160@60Hz for 2 external displays (with up to 7680 x 4320@30 Hz / 4096 x 2160@60Hz / 3840 x 2160@60Hz connected to one of the DisplayPorts) up to 3840 x 2160@30Hz (HDMI) / 3840 x 2160@60Hz (DP1 & DP2) for 3 external displays connected to 2 x DP and HDMI in parallel - w/o internal display on up to 3840 x 2160@30Hz (HDMI) / 3840 x 2160@60Hz (DP1 & DP2) for 3 external displays connected to 2 x DP and HDMI in parallel - with additional internal display on (4 displays in total)
Audio	1 Combo jack for headset usage
Ethernet (RJ-45)	1 (10/100/1000 Mbit/s, 2,5 Gbps) WoL up to S3 WoL from S0 to S5 state depending on connected Fujitsu mobile client PXE launching depending on connected Fujitsu mobile client Intel AMT (vPRO) with vPRO CPU on connected client User MAC address setting MAPT from 10th gen Downwards compatible to Thunderbolt™ 3 and Type-C (the client needs to have a Thunderbolt™ 3 or Type-C interface)
Notes	Number of simultaneous used displays and its possible resolutions and frequencies depend on mobile system and display interface type. Please consult always also the manual of the connected client.
Kensington Lock support	1
Interface Notes	2x Type-A - 5 V/0.9 A, 4.5 W 1x Type-A - 5 V/2.4 A, 12 W 2x Type-C - 5 V, 1.5 A/4.5 W charging port 1x Type-C - TBT™ 4 up to 60 W (PD v2.0-1.1), 5-20 V/3.0 A upstream (PC), Intel AMT support (vPRO) 1x Type-C - TBT™ 4 up to 15 W (PD v2.0-1.1), 5 V/3.0 A downstream, power output

Compliance

Europe	CE
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Dimensions / Weight / Environmental

Dimensions (W x D x H)	239 x 80 x 26 mm

Dimensions / Weight / Environmental	
Cable length	70 cm
Weight	400 g

Package content	
	Thunderbolt™ 4 Port Replicator including 170 W 3-pin AC adapter including TBT4 cable 70 cm w/o AC cable

Order code		
	FPCPR401BP	EAN: 4063872854948
Options	FPCCBM27BP Thunderbolt™ 4 active cable 200 cm length FPCCBM28BP Thunderbolt™ 4 cable 70 cm length	

Warranty	
Warranty Terms & Conditions	http://www.fujitsu.com/warranty
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

More information

Fujitsu products, solutions & services

In addition to Fujitsu Accessory Thunderbolt™ 4 Port Replicator, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio
Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products
www.fujitsu.com/global/products/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu Accessory Thunderbolt™ 4 Port Replicator, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/emeia/products/computing/peripheral/accessories

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.
Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.
Please find further information at http://www.fujitsu.com/global/about/environment

Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2022 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.
Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.
The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.