

1. Product and Company Identification

Material name Version # Issue date Product Code	HP Color LaserJet CC531A-AC Cyan Print Cartridge 01 09-May-2013 CC531A-AC
Company identification	Hewlett-Packard Company 3000 Hanover Street Palo Alto, CA 94304-1185 United States Telephone 650-857-1501
	Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209 (Direct) 1-503-494-7199 HP Customer Care Line (Toll-free within the US) 1-800-474-6836 (Direct) 1-208-323-2551 Email: hpcustomer.inquiries@hp.com

2. Hazards Identification

Potential health effects

otential health effects	
Eyes	May cause transient slight irritation
Skin	Unlikely to cause skin irritation.
Inhalation	Minimal respiratory tract irritation may occur with exposure to large amounts of toner dust. Use of this product as intended does not result in inhalation of excessive amounts of dust.
Ingestion	Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.

3. Composition / Information on Ingredients

Non-hazardous components	CAS #	Percent
Styrene acrylate copolymer	Trade Secret	<85
Wax	Trade Secret	<10
Pigment	Trade Secret	<6
Amorphous silica	7631-86-9	<2

4. First Aid Measures

First aid procedures	
Eye contact	Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at least 15 minutes or until particles are removed. If irritation persists, consult a physician.
Skin contact	Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation develops or persists.
Inhalation	Move person to fresh air immediately. If irritation persists, consult a physician.
Ingestion	Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, consult a physician.
General advice	No additional information
5. Fire Fighting Measures	
Flammable properties	Like most organic material in powder form, toner can form explosive dust-air mixtures when finely dispersed in air.

Extinguishing media		
Suitable extinguishing media	CO2, water, or dry chemical	
Unsuitable extinguishing media	None known.	
Fire fighting equipment/instructions	If fire occurs in the printer, treat as an	electrical fire.
Specific methods	None established.	
Hazardous combustion products	Carbon monoxide and carbon dioxide.	
6. Accidental Release Measu	ires	
Personal precautions	Minimize dust generation and accumula	tion.
Environmental precautions	Do not flush into surface water or sanit considerations.	ary sewer system. See also section 13 Disposal
Other information	damp cloth or vacuum cleaner. If a vac	to a bag or other sealed container. Clean remainder with a uum is used, the motor must be rated as dust explosive dust-air mixtures. Dispose of in compliance with
7. Handling and Storage		
Handling		inhalation of dust and contact with skin and eyes. Use om excessive heat, sparks, and open flames.
Storage	Keep out of the reach of children. Keep Store at room temperature.	tightly closed and dry. Store away from strong oxidizers.
8. Exposure Controls / Perso	onal Protection	
Occupational exposure limits		
US. NIOSH: Pocket Guide	o Chemical Hazards	
US. NIOSH: Pocket Guide Components	Туре	Value
US. NIOSH: Pocket Guide		Value 6 mg/m3
US. NIOSH: Pocket Guide Components Amorphous silica (CAS	Туре	6 mg/m3
US. NIOSH: Pocket Guide t Components Amorphous silica (CAS 7631-86-9)	TWA TWA USA OSHA (TWA/PEL): 15 mg/m3 (Tot	6 mg/m3
US. NIOSH: Pocket Guide t Components Amorphous silica (CAS 7631-86-9)	Type TWA USA OSHA (TWA/PEL): 15 mg/m3 (Tot ACGIH (TWA/TLV): 10 mg/m3 (Inhalab	6 mg/m3 al Dust), 5 mg/m3 (Respirable Fraction)
US. NIOSH: Pocket Guide to Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls	Type TWA USA OSHA (TWA/PEL): 15 mg/m3 (Tot ACGIH (TWA/TLV): 10 mg/m3 (Inhalat Amorphous silica: USA OSHA (TWA/PE mg/m3 Use in a well ventilated area.	6 mg/m3 al Dust), 5 mg/m3 (Respirable Fraction) le Particulate), 3 mg/m3 (Respirable Particulate)
US. NIOSH: Pocket Guide to Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment	Type TWA USA OSHA (TWA/PEL): 15 mg/m3 (Tot ACGIH (TWA/TLV): 10 mg/m3 (Inhalat Amorphous silica: USA OSHA (TWA/PE mg/m3 Use in a well ventilated area.	6 mg/m3 al Dust), 5 mg/m3 (Respirable Fraction) le Particulate), 3 mg/m3 (Respirable Particulate) L): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10
US. NIOSH: Pocket Guide to Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment General	Type TWA USA OSHA (TWA/PEL): 15 mg/m3 (Tot ACGIH (TWA/TLV): 10 mg/m3 (Inhalat Amorphous silica: USA OSHA (TWA/PE mg/m3 Use in a well ventilated area.	6 mg/m3 al Dust), 5 mg/m3 (Respirable Fraction) le Particulate), 3 mg/m3 (Respirable Particulate)
US. NIOSH: Pocket Guide to Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment	Type TWA USA OSHA (TWA/PEL): 15 mg/m3 (Tot ACGIH (TWA/TLV): 10 mg/m3 (Inhalat Amorphous silica: USA OSHA (TWA/PE mg/m3 Use in a well ventilated area.	6 mg/m3 al Dust), 5 mg/m3 (Respirable Fraction) le Particulate), 3 mg/m3 (Respirable Particulate) L): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10
US. NIOSH: Pocket Guide to Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment General	Type TWA USA OSHA (TWA/PEL): 15 mg/m3 (Tot ACGIH (TWA/TLV): 10 mg/m3 (Inhalat Amorphous silica: USA OSHA (TWA/PE mg/m3 Use in a well ventilated area.	6 mg/m3 al Dust), 5 mg/m3 (Respirable Fraction) le Particulate), 3 mg/m3 (Respirable Particulate) L): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10
US. NIOSH: Pocket Guide to Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment General 9. Physical & Chemical Prop	Type TWA USA OSHA (TWA/PEL): 15 mg/m3 (Tot ACGIH (TWA/TLV): 10 mg/m3 (Inhalat Amorphous silica: USA OSHA (TWA/PE mg/m3 Use in a well ventilated area. t No personal respiratory protective equi erties	6 mg/m3 al Dust), 5 mg/m3 (Respirable Fraction) le Particulate), 3 mg/m3 (Respirable Particulate) L): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10
US. NIOSH: Pocket Guide to Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment General 9. Physical & Chemical Prop Appearance	Type TWA USA OSHA (TWA/PEL): 15 mg/m3 (Tot ACGIH (TWA/TLV): 10 mg/m3 (Inhalat Amorphous silica: USA OSHA (TWA/PE mg/m3 Use in a well ventilated area. t No personal respiratory protective equi erties Fine powder	6 mg/m3 al Dust), 5 mg/m3 (Respirable Fraction) le Particulate), 3 mg/m3 (Respirable Particulate) L): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10
US. NIOSH: Pocket Guide to Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment General 9. Physical & Chemical Prop Appearance Physical state	Type TWA USA OSHA (TWA/PEL): 15 mg/m3 (Tot ACGIH (TWA/TLV): 10 mg/m3 (Inhalat Amorphous silica: USA OSHA (TWA/PE mg/m3 Use in a well ventilated area. t No personal respiratory protective equi erties Fine powder Solid.	6 mg/m3 al Dust), 5 mg/m3 (Respirable Fraction) le Particulate), 3 mg/m3 (Respirable Particulate) L): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10
US. NIOSH: Pocket Guide to Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment General 9. Physical & Chemical Prop Appearance Physical state Form	Type TWA USA OSHA (TWA/PEL): 15 mg/m3 (Tot ACGIH (TWA/TLV): 10 mg/m3 (Inhalab Amorphous silica: USA OSHA (TWA/PE mg/m3 Use in a well ventilated area. t No personal respiratory protective equi erties Fine powder Solid. solid	6 mg/m3 al Dust), 5 mg/m3 (Respirable Fraction) le Particulate), 3 mg/m3 (Respirable Particulate) L): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10
US. NIOSH: Pocket Guide to Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment General 9. Physical & Chemical Prop Appearance Physical state Form Color	Type TWA USA OSHA (TWA/PEL): 15 mg/m3 (Tot ACGIH (TWA/TLV): 10 mg/m3 (Inhalat Amorphous silica: USA OSHA (TWA/PE mg/m3 Use in a well ventilated area. Vo personal respiratory protective equi erties Fine powder Solid. solid Cyan	6 mg/m3 al Dust), 5 mg/m3 (Respirable Fraction) le Particulate), 3 mg/m3 (Respirable Particulate) L): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10

Negligible in water. Partially soluble in toluene and xylene.

Material name: CC531A-AC 10804 Version #: 01 Issue date: 09-May-2013

Melting point/Freezing point

pН

Vapor pressure

Vapor density

Boiling point

Solubility (water)

Not applicable

Not applicable

Not applicable

Not applicable

Not available.

Specific gravity	Not available.
Relative density	Not available.
-	
Flash point	Not applicable
Flammability limits in air, upper, % by volume	Not available.
Flammability limits in air, lower, % by volume	Not flammable
Auto-ignition temperature	Not applicable
Evaporation rate	Not applicable
Viscosity	Not applicable
Percent volatile	0 % estimated
Softening point	176 - 266 °F (80 - 130 °C)
VOC	Not available
Other information	No information available
Other data	
Decomposition temperature	>= 392 °F (>= 200 °C)
Oxidizing properties	No information available.
10. Chemical Stability & Re	activity Information

Chemical stability	Stable under normal storage conditions.
Conditions to avoid	Imaging Drum: Exposure to light
Incompatible materials	Strong oxidizers
Hazardous decomposition products	Carbon monoxide and carbon dioxide.
Possibility of hazardous reactions	Will not occur.

11. Toxicological Information

Toxicological data		
Components	Species	Test Results
Amorphous silica (CAS 7631-86-	9)	
Acute		
Oral		
LD50	Mouse	> 15000 mg/kg
	Rat	> 22500 mg/kg
Sensitization	Not classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and OSHA HCS (US).	
Chronic effects	No information available.	
Carcinogenicity	Not a known or suspected carcinogen according to any IARC Monograph, NTP, OSHA Regulations (USA), EU Directive, or Proposition 65 (California).	
Serious eye damage/eye irritation	Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU Directive 67/548/EEC and as amended.	
Mutagenicity	Negative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium)	
Reproductive effects	Not classified as toxic according to EU Directive 67/548/EEC and as amended, California Prop. 65, and DFG (Germany).	
Further information		t available for this specific formulation al health effects and Section 4 for first aid measures.

12. Ecological Information		
Ecotoxicological data		
Product	Species	Test Results
CC531A-AC Fish	LL50 Fish	> 1000 mg/l, 96 Hours
-		
Ecotoxicity Persistence and degradability	LL50: > 1000 mg/l, Fish, 96.00 Hours Not available.	
13. Disposal Considerations	5	
Disposal instructions		st-explosion prevention measures are taken. Finely
		mixtures in air. Dispose of in compliance with federal, state
		es recycling program enables simple, convenient recycling es. For more information and to determine if this service http://www.hp.com/recycle.
14. Transport Information		
15. Regulatory Information		
US federal regulations	US EPA TSCA Inventory: All chemical s under TSCA.	ubstances in this product comply with all rules or orders
Not regulated. CERCLA (Superfund) reportat None	rt Notification (40 CFR 707, Subpt. D) ble quantity Reauthorization Act of 1986 (SARA)	
	Reactivity Hazard - No	
SARA 302 Extremely hazardous substance	No	
SARA 311/312 Hazardous chemical	No	
Other information	No information available.	
Other regulations	under chemical substances notification	uct have been notified or are exempt from notification laws in the following countries: US (TSCA), EU (DSL/NDSL), Australia, Japan, Philippines, South Korea,
State regulations		
US. Massachusetts RTK - Not regulated. US. Pennsylvania RTK - H		
Not regulated. US. Rhode Island RTK Not regulated.		

16. Other Information	
HMIS® ratings	Health: 1 Flammability: 1 Physical hazard: 0
NFPA ratings	Health: 1 Flammability: 1 Instability: 0
Disclaimer	This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard Company. Data is the most current known to Hewlett-Packard Company at the time of preparatio of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.
Other information	This MSDS was prepared in accordance with USA OSHA Hazard Communications regulation (29 CFR 1910.1200).
Issue date	09-May-2013
This data sheet contains changes from the previous version in section(s):	11. Toxicological Information: Further information
Manufacturer information	Hewlett-Packard Company 11311 Chinden Boulevard Boise, ID 83714 USA (Direct) 1-503-494-7199 (Toll-free within the US) 1-800-457-4209

Explanation of abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act of 1986
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds