

Page:1/6

MSDS No.: MFP-2844

Product Name: TN512M, TN321M

Prepared date:4-Nov-2010 Revised Date: 10-May-2012

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: TN512M, TN321M used for: C554/C454/C364/C284/C224

Supplier Identification:

Konica Minolta Business Solutions Europe GmbH Europaallee 17, D-30855 Langenhagen, Germany Telephone: +49-(0)511-7404-272 Facsimile: +49-(0)511-7404-346

Emergency Telephone:

Information centre specialized on symptoms of poisoning Telephone: +49-30-19240

2. HAZARDS IDENTIFICATION Classification: Not classified as dangerous. (1999/45/EC)

Emergency Overview: Red powder (mean dia. is 5-10um by volume). Almost odorless

Most Important Hazards and Effects of the Products

Ingestion Effect:	None currently known.
Inhalation Effect:	None currently known. Minimal respiratory tract irritation may occur as with exposure
	to large amount of any non-toxic dust.
Eye Effect:	None currently known.
Skin Effect:	None currently known.
Chronic Effects:	Prolonged inhalation of excessive dusts may cause lung damage. Use of this
	product, as intended, does not result in inhalation of excessive dust.
Environment Hazard	s: No data are available on the adverse effects of this product on the environment.
Specific Hazards:	Dust explosion(like most finely divided organic powders)



Page:2/6

MSDS No.: MFP-2844

Product Name: TN512M, TN321M

Prepared date:4-Nov-2010 Revised Date: 10-May-2012

3. COMPOSITION / INFORMATION ON INGREDIENTS

Substance []

Preparation [X]

[Generic Name]	[CAS No.]	[%]
Styrene acrylic resin	+++	65-75
Ferrite Iron oxide	1309-37-1	5-15
. Manganese oxide	1344-43-0	1-10
Wax	+++	1-10
Organic pigment 1	+++	1-10
Organic pigment 2	+++	1-10
Amorphous silica	7631-86-9	1-10
Titanium dioxide	13463-67-7	1-10

ACGIH-TLV(USA): 0.2mg/m3
Worksafe-TWA(Austl): 1mg/m3
EEC-No.: 236-675-5
ACGIH-TLV(USA): 10mg/m3
IARC Monographs: Group 2B
R-Phrase(EC): Not listed

4. FIRST-AID MEASURES

Ingestion:	Wash out mouth with water. Drink one or two glasses of water. If symptoms occur, get medical attention.
Inhalation:	Move victim to fresh air immediately. If symptoms occur, get medical attention.
Eye Contact:	Immediately flush eyes with plenty of water for 15 minutes. If symptoms occur, get medical attention.
Skin Contact:	Wash with water and mild soap.

Worksafe-TWA(Austl): 10mg/m3

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: CO2, water spray, foam and dry chemical Extinguishing Media to Avoid: Full water jet Fire and Explosion Hazards: If dispersed in air, like most finely divided organic powders, may form an explosive mixture. Protection of Firefighters: Use self-contained breathing apparatus(SCBA).



Page:3/6

MSDS No.: MFP-2844

Product Name: TN512M, TN321M

Partition Coefficient, n-Octanol/Water:

Prepared date:4-Nov-2010 Revised Date: 10-May-2012

	Revised Date: 10-May-2012
6. ACCIDENTAL RELEASE MEASURES	
Personal Precautions: None	
Environmental Precautions: None	
Methods for Cleaning Up: Wear personal protective eq	uipment(See Section 8). Vacuum or sweep material
	for waste disposal. Use vacuum equipped with High
	PA) filter. Vacuum should be electrically bonded and
-	ectricity. To avoid dust generation, do not sweep dry.
7. HANDLING AND STORAGE	
Handling	
Technical Measures: None	
Precautions: Do not breathe dust. Avoid	contact with ever
Safe Handling Advice: Try not to disperse the part	-
Storage Technical Measures: None	
	re in a cool and dry place. Keep out of reach of children.
Incompatible Products: None	re in a cool and dry place. Reep out of reach of children.
Packaging Materials: Bottles or Cartridge design	ated by Konica Minolta
	DTECTION
Engineering Measures	
Ventilation: None required with intended use.	
Control Parameters(As total dust)	
ACGIH-TLV(USA) : 10mg/m3 (Inhalable pai	rticles), 3.0 mg/m3 (Respirable particles)
OSHA-PEL(USA): 15mg/m3 (Total dusts),	5.0 mg/m3 (Respirable fraction)
DFG-MAK(GER): 4mg/m3 (Inhalable frac	ction), 1.5mg/m3 (Respirable fraction)
Worksafe-TWA(Austl.): 10mg/m3	
Personal Protective Equipment	
Not required under normal conditions. For use oth	ner than in normal operating procedures (such as in the
event of large spill), goggles and respirators may be	
Hygiene Measures: Wash hands after handling.	
9. PHYSICAL AND CHEMICAL PROPERTI	ES
Appearance	
5	Color: Red
Form: Powder (mean dia. is 5-10um by volume)	
	lmost odorless
	lot applicable
- <i>· · · ·</i>	lot applicable
Melting Point(°C):	round 125C(275F) (Softening Point)
Flash Point(°C):	lot applicable
Ignition Temperature(°C):	lo data available
Explosion Properties: N	lo data available
Vapor Pressure: N	lot applicable
Specific Gravity: 1.	2
Solubility: Ir	nsoluble in water.
-	at an all a bla

Not applicable



Page:4/6

MSDS No.: MFP-2844

Product Name: TN512M, TN321M

Prepared date:4-Nov-2010 Revised Date: 10-May-2012

10. STABILITY AND REACTIVITY

Stability:	Stable except above 200C(392F).		
Hazardous Reactions:	Dust explosion, like most finely divided organic powders.		
Conditions to avoid:	Electric discharge, throwing into fire.		
Materials to Avoid:	Oxidizing materials.		
Hazardous Decomposition Products: CO, CO2, NOx and smoke.			
Hazardous Polymerization:	Will not occur.		

11. TOXICOLOGICAL INFORMATION

Acute Toxicity:

Ingestion(oral), LD50(mg/kg):	>2000 (Rat) *	
Dermal, LD50(mg/kg):	No data available	
Inhalation, LC50(mg/l):	>5.06 (Rat,4hour) *(This was the highest attainable concentration.)	
Eye irritation:	Minimal irritant (Rabbit) *	
Skin irritation:	None irritant (Rabbit) *	
Skin sensitizer:	Non sensitizer (Mouse) *	
Least Effected as Obrania Taxiaity and an a tama Taxiaity		

Local Effects: see Chronic Toxicity or Long term Toxicity

Chronic Toxicity or Long Term Toxicity:

Prolonged inhalation of excessive dust may cause lung damage. It is attributed to "lung overloading", a generic response to excessive amounts of any dust retained in the lungs for a prolonged interval. Use of this product, as intended, does not result in inhalation of excessive dust.

In a study in rats by chronic inhalation exposure to a typical toner, a mild to moderate degree of lung fibrosis was observed in 92% of rats in the high concentration(16mg/m³) exposure group, and a minimal to mild degree of fibrosis was noted in 22% of the animals in the middle(4mg/m³) exposure group. But no pulmonary change was reported in the lowest(1mg/m³) exposure group, the most relevant level to potential human exposures.

Carcinogenicity

The IARC reevaluated titanium dioxide as a Group 2B carcinogen (possible human carcinogen). In animal chronic inhalation studies, the tumor formulation observed in only rats with animal chronic inhalation study are attributed to "lung overloading", a generic response to excessive amounts of any dust retained in the lungs for a prolonged interval. Use of this product, as intended, dose not result in inhalation of excessive dust. Epidemiological study to date have not revealed any evidence of the relation between exposure to titanium dioxide and diseases of the respiratory tract beyond general effects of dust.

Mutagenicity:	Negative * (AMES test)
Teratogenicity:	No data available

(*= Based on data for other Konica Minolta Products with similar ingredients)



Page:5/6

Product Name: TN512M, TN321M

MSDS No.: MFP-2844

Prepared date:4-Nov-2010 Revised Date: 10-May-2012

12. ECOLOGICAL INFORMATION

No data are available on the adverse effects of this material on the environment. Ecotoxicity: No data available Mobility: No data available Persistence and degradability: No data available Bioaccumulative potential: No data available

13. DISPOSAL CONSIDERATION

When disposing of the waste or recovered material, consult federal, state and/or local regulations for the proper disposal method.

14. TRANSPORT INFORMATION

Information on Code and Classifications According to International Regulations UN Classification: None

15. REGULATORY INFORMATION

US Information

Information on the label: Not required

TSCA(Toxic Substances Control Act):

All chemical substances in this product comply with all applicable rules or order under TSCA.

California Proposition 65:

This product contains no chemical substances subject to California Proposition 65.

EU Information

Information on the label (1999/45/EC and 67/548/EEC): Not required

Article14 (2.1) of Directive 1999/45/EC is not applicable to this product.

16. OTHER INFORMATION

HMIS Rating: The National Paint and Coating Association(USA): Health: 1 Flammability: 1 Reactivity: 0 Recommended Uses: Toner for Electrophotographic Equipment

Explanation of term: IARC 2B means "possible human carcinogen".

Revision Information: Regular revision on revised date.

Literature References:

ANSI Z400.1-1993

ISO 11014-1

Commission Directive 91/155/EEC

IARC(2010): IARC monographs on the Evaluation of the Carcinogenic Risk of Chemicals to Humans, Vol. 93, Carbon Black, Titanium Dioxide, and Talc, Lyon, pp. 193-276

H.Muhle, B.Bellmann, O.Creutzenberg, C.Dasenbrock, H.Ernst, R.Kilpper, J.C.MacKenzie, P.Morrow, U.Mohr, S.Takenaka, and R.Mermelstein(1991)

Pulmonary Response to Toner upon Chronic Inhalation Exposure in Rats. Fundamental and Applied Toxicology 17, pp.280-299.

NIOSH CURRENT INTELLIGENCE BULLETIN : Evaluation of Health Hazard and Recommendation for Occupational Exposure to Titanium Dioxide :DRAFT



Page:6/6

MSDS No.: MFP-2844

Product Name: TN512M, TN321M

Prepared date:4-Nov-2010 Revised Date: 10-May-2012

Restrictions:

The above information is believed to be accurate and represents the best information currently available to Our Corporation. However, Our Corporation makes no warranty with respect to such information, and Our Corporation assumes no liability resulting from its use. Users should make their own investigation to determine the suitability of the information for their particular purposes.