Panasonic Communications Co., Ltd. Document Solutions Company

9-1 Hiraide Industrial Park, Utsunomiya City, Tochigi, 321-8502 Japan TEL: Japan (0) 28-663-3285, FAX: Japan (0) 28-662-8393

Material Safety Data Sheet

Page: 1 of 3

MSDS No.: 021-000948

Date : ____ 18 August, 2008

SECTION 1 PRODUCT IDENTIFICATION

Product Name: Toner of Toner Cartridge UG-3380 for Panasonic Facsimile machines

Models UF-6300 & UF-5300

Product No.: Toner for Toner Cartridge UG-3380

SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

	INGREDIENTS (Common Name)	CAS #	PROPORTION (% by wt.)	OSHA PEL	ACGIH TLV	OTHER LIMITS
•	Polystyrene Acrylate copolymer		> 54.0	None established	None established	None
•	Iron oxide	1317-61-9	< 40.0	None established	None established	None
•	Polypropylene		< 4.0	None established	None established	None
•	Organic pigment		< 1.0	None established	None established	None
•	Amorphous silica*		< 1.0	20mppcf	$10.0~\mathrm{mg/m}^3$	None

Ethanol, 2-ethoxy- [CAS # 110-80-5] contained less than 0.01wt% in this product. *: See [Section 15]

SECTION 3 HAZARDOUS IDENTIFICATION

EMERGENCY OVERVIEW :

Odorless black fine powder.

Not a highly flammable, but when suspended in air, is combustible as with most organic powders.

POTENTIAL HEALTH EFFECTS :

EYES: Solid or dusts may cause irritation or corneal injury.

SKIN CONTACT: Essentially nonirritating to skin.

SKIN ABSORPTION: Skin absorption is unlikely due to physical properties.

INGESTION: Oral toxicity is believed to be low.

INHALATION: Minimal irritation to respiratory track may occur.

FIRE AND EXPLOSION :

SENSITIVITY TO MECHANICAL IMPACT : None SENSITIVITY TO STATIC CHARGE : None

Page: 2 of 3 MSDS No.: 021-000948

SECTION 4 FIRST AID MEASURES

EYES: Flush eyes immediately with plenty of water for at least 15 minutes.

SKIN: Flush with plenty of water. Use soap.

INGESTION: No adverse effects anticipated by this route of exposure incidental

to proper handling.

INHALATION: Remove to fresh air. If effects occur, consult medical personnel.

SECTION 5 FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES :

FLASH POINT : No data available

FLAMMABLE LIMITS

Explosion Limits(Upper): No data available
Explosion Limits(Lower): No data available

EXTINGUISHING MEDIA: Water fog, foam, CO₂, dry chemical.

FIRE-FIGHTING EQUIPMENT: Wear full bunker gear including a positive pressure

self-contained breathing apparatus in case of burning

in large quantities.

SECTION 6 ACCIDENTIAL RELEASE MEASURES

Minimize the release of particulates. Wear personal protective equipment. Do not use vacuum cleaner.

After by lightly spraying with water to prevent development of dust, spills should be swept up or wiped up. Then residuals can be removed with soap and water. Preferred to use the material in a place, covering up the floor and surrounding matters with suitable sheets such as paper, in a case of being not fit to scrub the floor with water. These used sheets should be wrapped up in spills and transfer into a suitable container for disposal.

Garments may be washed or dry cleaned, after removal of loose toner.

SECTION 7 HANDLING AND STORAGE

Avoid creating dust. Clean up all spills promptly.

Inhalation and contact with skin or eyes should be avoided.

Provide general ventilation. Good general ventilation should be sufficient for most conditions.

Store in cool, well ventilated place away from flames and spark-producing equipment. May toners be preferred to use or to handle at the suitable place without concerning about smudges to which are given rise by releasing them.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES: ACGIHTLV=10mg/m³(Total dust), 3mg/m³(Respirable dust)

OSHA PEL= 15mg/m³(Total dust), 5mg/m³(Respirable dust)

RESPRIRATORY PROTECTION: For most conditions, no respiratory protection should

be needed; however, in dusty atmospheres, use an

approved dust respirator.

SKIN PROTECTION: No precautions should be needed under normal use. EYE PROTECTION: No precautions should be needed under normal use.

Page: 3 of 3 MSDS No.: 021-000948

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Black fine powder

ODOR: Odorless

BOILING POINT (°C): Not applicable VAPOR PRESSURE (mg Hg.): Not applicable VAPOR DENSITY (AIR = 1): Not applicable SOLUBILITY IN WATER: Negligible SPECIFIC GRAVITY (H₂O=1): ca. 1.6

MELTING POINT (°C): No data available pH: Not applicable PERCENT VOLATILE: Not applicable

SECTION 10 STABILITY AND REACTIVITY

STABILITY: This is a stable product.

INCOMPATIBILITY: (SPECIAL MATERIALS TO AVOID)

Strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon oxides, hydrocarbons (by high heat

and fire)

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

Mutagenicity: Negative in the Ames Test

Carcinogenicity: No data available Chronic Effects: No data available

SECTION 12 ECOLOGICAL INFORMATION

None

SECTION 13 DISPOSAL CONSIDERATION

WASTE DISPOSAL METHOD: Waste must be disposed of in accordance with country

and local environmental control regulations.

SECTION 14 TRANSPORT INFORMATION

TRANSPORT INFORMATION: This is not a hazardous product.

UN No.: None allocated.

SECTION 15 REGULATORY INFORMATION

USA INFORMATION :

All chemical substances in this product comply with all applicable rules or orders under TSCA.

SARA Title III Section 313 :

Organic pigment is regarded as Chromium compounds (category codes: N090).

AUSTRALIA INFORMATION :

Not classified as hazardous according to criteria of NOHSC.

SECTION 16 OTHER INFORMATION

NFPA rating: Health = 1, Flammability = 1, Reactivity = 0

Information on this data sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions.