

UniFi® Network



UniFi 6 Long-Range Access Point



U6-LR is a High-Performance Access Point leveraging advanced WiFi 6 technology to provide powerful wireless coverage to enterprise environments. It delivers an aggregate radio rate of up to 3.0 Gbps with 5 GHz WiFi 6 (4x4 MU-MIMO and OFDMA) and 2.4 GHz 4x4 MIMO radios. The U6-LR seamlessly blends into any environment, and is capable of being mounted in indoor and semi-outdoor environments (IP54 rated), and comes equipped with a Bluetooth Low Energy Radio for location based services.

Mechanical

| | |
|--------------------|---|
| Dimensions | Ø220 x 48 mm (Ø8.66 x 1.89") |
| Weight | Without Mount: 800 g (1.76 lb) With Mount: 930 g (2.05 lb) |
| Enclosure Material | Plastic |
| Mounting Material | SGCC Steel |
| Weatherproofing | IP54 |

Hardware

| | | |
|-------------------------|--|-----------|
| Processor Specs | Dual-Core® Cortex® A53 at 1.35 GHz | |
| Memory Information | 512 MB | |
| Management Interface | Ethernet | |
| Networking Interface | (1) 1 Gbps Ethernet RJ45 | |
| Button | Factory Reset | |
| LED | RGB | |
| Power Method | PoE+, Passive PoE (48V) | |
| Power Supply | UniFi PoE Switch 48V, 0.5A PoE Adapter (Not Included) | |
| Supported Voltage Range | 44 to 57VDC | |
| Max. Power Consumption | 16.5W | |
| Max. TX Power | 2.4 GHz | 26 dBm |
| | 5 GHz | 26 dBm |
| MIMO | 2.4 GHz | 4 x 4 |
| | 5 GHz | 4 x 4 |
| Throughput Speeds | 2.4 GHz | 600 Mbps |
| | 5 GHz | 2400 Mbps |
| Antenna Gain | 2.4 GHz | 4 dBi |
| | 5 GHz | 5.5 dBi |
| Mounting | Wall/Ceiling (Kits Included) | |
| Operating Temperature | -30 to 60° C (-22 to 140° F) | |
| Operating Humidity | 5 - 95% Noncondensing | |
| Certifications | CE, FCC, IC | |



Software

| | |
|-------------------------|---|
| Wi-Fi Standards | 802.11a/b/g Wi-Fi 4/Wi-Fi 5/Wi-Fi 6 |
| Wireless Security | WPA-PSK, WPA-Enterprise (WPA/WPA2/WPA3*) <small>*Supported With Upcoming Controller Versions</small> |
| BSSID | 8 per Radio |
| VLAN | 802.1Q |
| Advanced QoS | Per-User Rate Limiting |
| Guest Traffic Isolation | Supported |
| Concurrent Clients | 300+ |

Supported Data Rates (Mbps)

| | |
|--------------------|---|
| 802.11a | 6, 9, 12, 18, 24, 36, 48, 54 Mbps |
| 802.11b | 1, 2, 5.5, 11 Mbps |
| 802.11g | 6, 9, 12, 18, 24, 36, 48, 54 Mbps |
| 802.11n (Wi-Fi 4) | 6.5 Mbps to 600 Mbps (MCS0 - MCS31, HT 20/40) |
| 802.11ac (Wi-Fi 5) | 6.5 Mbps to 1.7 Gbps (MCS0 - MCS9 NSS1/2/3/4, VHT 20/40/80/160) |
| 802.11ax (Wi-Fi 6) | 7.3 Mbps to 2.4 Gbps (MCS0 - MCS11 NSS1/2/3/4, HE 20/40/80/160) |



Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at www.ui.com/support/warranty

©2020 Ubiquiti Inc. All rights reserved. Ubiquiti, Ubiquiti Networks, the Ubiquiti U logo, the Ubiquiti beam logo, UniFi, and UniFi Network are trademarks or registered trademarks of Ubiquiti Inc. in the United States and in other countries. All other trademarks are the property of their respective owners.